

# Hoogcentrifugerend



6.5 kg  
8.0 kg  
11.0kg  
14.0kg  
18.0kg  
24.0kg  
28.0kg  
33.5kg  
40 kg  
52 kg  
80 kg  
100 kg  
120 kg

## SERIOUS ABOUT LAUNDRY.

UY-SERIES

**Tindie**  
Mac

## UY SERIES SOFTMOUNT WASHER-EXTRACTORS 6.5-120.0 KG – PROFORM CONTROL

MODELS	UY65	UY80	UY105	UY135	UY180	UY240	
Control	PROform	PROform	PROform	PROform	PROform	PROform	
Capacity kg (lb)	6.5 (14)	8 (20)	11 (25)	14 (30)	18 (40)	24 (55)	
Tilt Option	N/A	N/A	N/A	N/A	N/A	N/A	
<b>Dimensions w/o Tilt</b>							
Width mm (in)	710 (27 15/16)	710 (27 15/16)	795 (31 5/16)	795 (31 5/16)	970 (38 3/16)	970 (38 3/16)	
Depth mm (in)	740 (29 1/8)	790 (31 1/8)	795 (31 5/16)	945 (37 3/16)	970 (38 3/16)	1105 (43 1/2)	
Height mm (in)	1115 (43 7/8)	1115 (43 7/8)	1225 (48 1/4)	1225 (48 1/4)	1410 (55 1/2)	1410 (55 1/2)	
<b>Dimensions w/ Tilt</b>							
Width mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	
Depth mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	
Height mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	
Cylinder Diameter mm (in)	530 (20 7/8)	530 (20 7/8)	620 (24 3/8)	620 (24 3/8)	750 (29 1/2)	750 (29 1/2)	
Cylinder Depth mm (in)	305 (12)	350 (13 3/4)	350 (13 3/4)	450 (17 3/4)	410 (16)	545 (21 1/2)	
Cylinder Volume litres (Cu.ft.)	65 (2.3)	75 (2.6)	105 (3.7)	135 (4.8)	180 (6.4)	240 (8.5)	
Door opening size mm (in)	330 (13)	330 (13)	410 (16 1/8)	410 (16 1/8)	460 (18 1/8)	460 (18 1/8)	
Door Bottom to Floor mm (in)	349 (13 3/4)	349 (13 3/4)	342 (13 1/2)	342 (13 1/2)	477 (18 3/4)	477 (18 3/4)	
Wash Speed RPM	49	49	49	49	42	42	
Extract Speed RPM	1165	1165	1075	1075	980	980	
Extract G-Force	400	400	400	400	400	400	
Water Inlet Conn. mm (in)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	2 x 19 (3/4)	
Steam Inlet Conn. mm (in)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	
Drain Conn. Size mm (in)	76 (3)	76 (3)	76 (3)	76 (3)	76 (3)	76 (3)	
Motor Size kW (HP)	0.75 (1.00)	0.75 (1.00)	1.10 (1.48)	1.50 (2.01)	2.20 (2.95)	3.00 (4.02)	
Voltage/Hz/Phase	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V+N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph
<b>Shipping Dimensions w/o Tilt</b>							
Height mm (in)	1235 (48 5/8)	1235 (48 5/8)	1340 (52 3/4)	1340 (52 3/4)	1550 (61)	1550 (61)	
Width mm (in)	735 (28 15/16)	735 (28 15/16)	820 (32 1/4)	820 (32 1/4)	1020 (40 3/16)	1020 (40 3/16)	
Depth mm (in)	825 (32 1/2)	825 (32 1/2)	825 (32 1/2)	970 (38 3/16)	1010 (39 6/8)	1150 (45 1/4)	
<b>Shipping Dimensions w/ Tilt</b>							
Height mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	
Width mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	
Depth mm (in)	N/A	N/A	N/A	N/A	N/A	N/A	
Net Weight kg (lb) w/o tilt	170 (375)	185 (408)	210 (463)	255 (563)	380 (838)	430 (948)	
Net Weight kg (lb) w/ tilt	N/A	N/A	N/A	N/A	N/A	N/A	
Shipping Weight kg (lb) w/o tilt	180 (397)	200 (441)	235 (518)	275 (606)	395 (871)	450 (992)	
Shipping Weight kg (lb) w/ tilt	N/A	N/A	N/A	N/A	N/A	N/A	
Agency Approvals	CE, CSA	CE, CSA	CE, CSA	CE, CSA	CE, CSA	CE, CSA	

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

UY280	UY335	UY400	UY520	UY800	UY1000	UY1200
PROform	PROform	PROform	PROform	PROform	PROform	PROform
28 (65)	33.5 (75)	40 (90)	51.8 (125)	80.7 (180)	100.3 (230)	120 (275)
N/A	N/A	Option	Option	Option	Option	Option
970 (38 3/16)	1195 (47)	1195 (47)	1195 (47)	1495 (58 7/8)	1790 (70 1/2)	1855 (73)
1185 (46 5/8)	1330 (52 3/8)	1430 (56 1/2)	1610 (63 3/8)	1940 (76 3/8)	2005 (78 15/16)	2085 (82 1/16)
1410 (55 1/2)	1905 (75)	1905 (75)	1905 (75)	2010 (79 1/8)	2060 (81 1/8)	2085 (82 1/8)
N/A	N/A	1328 (52 1/4)	1328 (52 1/4)	1565 (61 5/8)	1851 (72 7/8)	1894 (74 9/16)
N/A	N/A	1941 (76 7/16)	2053 (80 13/16)	2380 (93 11/16)	2534 (99 3/4)	2553 (100 1/2)
N/A	N/A	2368 (93 1/4)	2381 (93 3/4)	2476 (97 1/2)	2575 (101 3/8)	2628 (103 1/2)
750 (29 1/2)	914 (36)	914 (36)	914 (36)	1110 (43 11/16)	1200 (47 1/4)	1300 (51 3/16)
620 (24 1/2)	510 (20)	610 (24)	790 (31.1)	838 (33)	860 (33 7/8)	870 (34 1/4)
280 (9.9)	335 (11.8)	400 (14.1)	518 (18.3)	807 (28.5)	1003 (35.4)	1180 (41.7)
460 (18 1/8)	540 (21 5/16)	540 (21 5/16)	540 (21 5/16)	530 (20 7/8)	530 (20 7/8)	650 (25 5/8)
477 (18 3/4)	730 (28 3/4)	730 (28 3/4)	730 (28 3/4)	750 (29)	820 (32 1/4)	775 (30 1/2)
42	38	38	38	36	33	32
915	830	830	830	750	720	695
350	350	350	350	350	350	350
2 x 19 (3/4)	3 x 25 (1)	3 x 25 25 (1)	3 x 25 25 (1)	3 x 38 (1 1/2)	3 x 38 (1 1/2)	3 x 38 (1 1/2)
13 (1/2)	19 (3/4)	19 (3/4)	19 (3/4)	25 (1)	25 (1)	25 (1)
76 (3)	2 x 76 (3)	2 x 76 (3)	2 x 76 (3)	2 x 103 (4)	2 x 103 (4)	2 x 103 (4)
3.00 (4.02)	4.00 (5.36)	7.50 (10.06)	7.50 (10.06)	11.00 (14.75)	15.00 (20.12)	18.50 (24.81)
200-240V 50/60Hz 1ph 200-240V 50/60Hz 3ph 380-415V + N 50/60Hz 3ph 380-415V 50/60Hz 3ph 440-480V 50/60Hz 3ph	200-240v/50-60Hz/3 380-415V/50-60Hz/3 440-480V/50-60Hz/3	200-240v/50-60Hz/3 380-415V/50-60Hz/3 440-480V/50-60Hz/3	200-240v/50-60Hz/3 380-415V/50-60Hz/3 440-480V/50-60Hz/3	200-240v/50-60Hz/3 380-415V/50-60Hz/3 440-480V/50-60Hz/3	200-240v/50-60Hz/3 380-415V/50-60Hz/3 440-480V/50-60Hz/3	200-240v/50-60Hz/3 380-415V/50-60Hz/3 440-480V/50-60Hz/3
1550 (61)	2105 (82 15/16)	2105 (82 15/16)	2105 (82 15/16)	2200 (86 5/8)	2345 (92 5/16)	2340 (92 1/8)
1020 (40 3/16)	1430 (56 1/4)	1430 (56 1/4)	1430 (56 1/4)	1690 (66 1/2)	1865 (73 7/16)	2000 (78 3/4)
1230 (48 7/16)	1475 (58 1/8)	1570 (61 3/4)	1750 (68 15/16)	1950 (76 3/4)	2125 (83 11/16)	2170 (85 7/16)
N/A	N/A	2350 (92 1/2)	2350 (92 1/2)	2440 (96 1/16)	2490 (98)	2490 (98)
N/A	N/A	1440 (56 11/16)	1440 (56 3/4)	1690 (66 1/2)	2040 (80 5/16)	2040 (80 5/16)
N/A	N/A	1760 (69 1/4)	1760 (69 1/4)	2075 (81 11/16)	2375 (93 1/2)	2375 (93 1/2)
495 (1092)	1190 (2623)	1560 (3439)	1630 (3594)	2640 (5820)	3170 (6989)	3480 (7672)
N/A	N/A	1735 (3825)	1810 (3991)	2990 (6592)	3520 (7761)	3840 (8466)
515 (1135)	1310 (2888)	1700 (3748)	1770 (3902)	2830 (6239)	3410 (7518)	3710 (8179)
N/A	N/A	1875 (4134)	1950 (4300)	3210 (7077)	3760 (8290)	4060 (8951)
CE, CSA	CE	CE	CE	CE	CE	CE

To learn more

Bedrijfswasapparatuur, importeur Unimac & Speedqueen

**GOUD**  
Laundry Solutions  
Industriële wasapparatuur

**André Goud**  
Group Sales Manager

Paukenslag 1  
3286TD Klaaswaal  
Nederland  
tel: +31(0)186-576050 - +31(0)186-575075  
Mobile: +31(0)620607465  
andre@laundrysolutions.nl

www.laundrysolutions.nl

Alliance International – Nieuwstraat 146, B-8560 Wevelgem, Belgium +32 56 41 20 54



UniMac is a division of Alliance Laundry Systems. Based in Ripon, Wis., USA and Wevelgem Belgium, Alliance is the world's leading manufacturer of commercial laundry equipment. Learn more at [alliancelaudry.com](http://alliancelaudry.com)

A114-0049  
©2014 Alliance Laundry Systems LLC



SERIOUS ABOUT LAUNDRY.